
DIODE DYNAMICS

PERFORMANCE LIGHTING TECHNOLOGY

2015-2017 Ford Mustang Demon Eye Bracket Mounting Instructions

Thank you for your purchase of this unique product for your Ford Mustang! Designed specifically for the 2015-2017 Ford Mustang, our Mustang Demon Eye Bracket allows you to mount a demon eye inside your headlight without having to open it!

Tools Needed: Torx T20 Screwdriver, Phillips Screwdriver





1. Mount the Demon Eye to the bracket. Be sure the Demon Eye is facing out with the Diode Dynamics engraving on the bracket as shown in the picture to the left.



2. Remove the bumper and headlamp from the vehicle. Next, mount the demon eye in the headlamp. To do so, remove the 4 screws holding the HID ballast in place using a T20 Torx bit.



3. Unclip the HID connector and pull straight out on the HID ballast. Set it aside to provide enough working space to get inside in the headlamp. Then remove the Phillips screw holding the factory circuit board down.

See back for further instructions.



2015-2017 Ford Mustang Demon Eye Bracket Mounting Instructions



- 4. Place the bracket and Demon Eye into the projector housing. The pressure fitted tab should be placed in the lower hole and lock into place.
- 5. The hole on the Demon Eye bracket should be placed over the screw hole on the circuit board. See picture to the left.



6. Replace the original screw. Do not over tighten.



- 7. Route the Demon Eye wire out before reconnecting and replacing the HID ballast using the original screws.
- 8. Repeat the process for the other headlamp. Finish your wiring. Test thoroughly and reinstall the headlamps onto the vehicle.

NEED MORE HELP?

Scan the QR code to link to our installation video online!

We've taken the time to test our products on your vehicle. We can guarantee compatibility and fitment the first time – no guessing game! If you need more help with installation, watch our step-by-step video to walk you through the process.





Please contact **Diode Dynamics** should you have any questions about the installation or wiring process, at **314-205-3033** (9a-5p CST) or **contact@diodedynamics.com.**

















